

### XF043

Project	
Item	
Quantity	
Date	

Model	
LINEMICRO™	

Convectio	n oven	Electric
4 trays 600x400		Drop down opening
Knob		
Voltage:	380-415V 3N~ / 2	220-240V 3~ / 220-240V 1~

#### Description

Convection oven with analogical control and stainless steel cooking chamber. It allows to set the cooking time and temperature. Ideal for frozen bakery and pastry products for breakfast and fast foods. The AIR.Plus technology guarantees perfect cooking uniformity on all baking trays.



## **Standard cooking features**Manual cooking

• Temperature: 80 °C - 260 °C

# Advanced and automatic cooking features Unox Intensive Cooking

- DRY.Plus: rapidly extracts humidity from the cooking chamber
- AIR.Plus: multiple fans with reverse gear and 2 speed settings


#### **Key features**

- Cooking chamber in high-resistance AISI 430 steel with rounded edges
- Double glass
- Oven chamber lighting with halogen lamp
- Baking chamber with chrome-plated steel rack rails





## XF043



#### **Dimensions and weight**

Width	800 mm
Depth	707 mm
Height	472 mm
Net weight	44 kg
Tray pitch	70 mm

#### **Connection positions**

2	Terminal board power supply
3	Unipotential terminal
6	Technical data plate
7	Safety thermostat
12	Hot fumes exhaust chimney



### XF043

#### **Electrical power supply**

#### **STANDARD**

STANDARD	
Voltage	380-415 V
Phase	~3PH+N+PE
Frequency	50 Hz
Total power	5,3 kW
Max Amp draw	13 A
Required breaker size	16 A
Power cable requirements*	5G x 1,5 mm^2
Plug	NOT INCLUDED
OPTION A	
Voltage	220-240 V
Phase	~3PH+PE
Frequency	50 Hz
Total power	5,3 kW
Max Amp draw	13 A
Required breaker size	16 A
0.20	
Power cable requirements*	4G x 2,5 mm^2
Power cable	4G x 2,5 mm^2 NOT INCLUDED
Power cable requirements*	
Power cable requirements*	
Power cable requirements* Plug OPTION B	NOT INCLUDED
Power cable requirements* Plug OPTION B Voltage	NOT INCLUDED  220-240 V
Power cable requirements* Plug OPTION B Voltage Phase	NOT INCLUDED  220-240 V ~1PH+PE
Power cable requirements* Plug OPTION B Voltage Phase Frequency	NOT INCLUDED  220-240 V ~1PH+PE  50 Hz
Power cable requirements* Plug OPTION B Voltage Phase Frequency Total power	NOT INCLUDED  220-240 V  ~1PH+PE  50 Hz  5,3 kW
Power cable requirements* Plug OPTION B Voltage Phase Frequency Total power Max Amp draw Required breaker	NOT INCLUDED  220-240 V ~1PH+PE  50 Hz  5,3 kW  23 A
Power cable requirements* Plug OPTION B Voltage Phase Frequency Total power Max Amp draw Required breaker size Power cable	NOT INCLUDED  220-240 V ~1PH+PE  50 Hz  5,3 kW  23 A

<sup>\*</sup>Recommended size - observe local ordinance.

#### Accessories

- Baking Essentials: special trays
- SPRAY&Rinse: Practical spray detergent to manually clean all kinds of oven. It degreases and removes all kind of dirt

#### **Installation requirements**

Installations must comply with all local electrical systems, particularly as for minimum wire gauge required for field connection, hydraulic and ventilation supply. Exhaust and fume analysis must be performed in case of gas ovens.

Register to DDC Service to access data and product specifications.