

CHAMBER VACUUM PACKERS TOP CAM900TC

SKU: CAM900TC



ADDITIONAL INFORMATION

Potenza Kw	<u>2 kW (2 HP)</u>
Alimentazione	<u>230-400V/3N/50Hz</u>
Barra saldante	<u>1 x 500mm – 1 x 900mm</u>
Pompa vuoto	<u>63 m³/h</u>
Vuoto max ottenibile	<u>98%</u>
Dimensioni utili della camera	<u>920 x 570 x 220(h) mm</u>
Dimensioni macchina (l x l x h mm)	<u>1040 x 680 x 1050(h) mm</u>
Peso netto (kg)	<u>180</u>
Peso lordo (Kg)	<u>205</u>
Dimensioni imballo (l x l x h mm)	<u>1100 x 800 x 1150(h) mm</u>
Volume imballo (m3)	<u>1.012</u>

Machine aimed at prolonging food preservation times, keeping intact the organoleptic characteristics and preventing the proliferation of bacteria at low temperatures. Stainless steel AISI 304 casing and internal bowl - bowl with rounded corners - plexiglass lid - automatic lid opening at the end of the cycle - LCD control panel with 20 storable programs - oil cleaning function in the pump and soft air function standard included. - piston sealing system with removable sealing bar without cables - provision for inert gas injection - BUSH pump (made in Germany) - "step vac" and "extra vacuum" functions included. Wheeled models.



