

CHAMBER VACUUM PACKERS TOP CAM500TC

SKU: CAM500TC



ADDITIONAL INFORMATION

Potenza Kw	<u>1,1 kW (1,5 HP)</u>
Alimentazione	<u>230V/1N/50-60Hz</u>
Barra saldante	<u>500 mm</u>
Pompa vuoto	<u>20 m³/h</u>
Vuoto max ottenibile	<u>98%</u>
Dimensioni utili della camera	<u>520 x 520 x 220(h) mm</u>
Dimensioni macchina (l x l x h mm)	<u>610 x 630 x 1050(h) mm</u>
Peso netto (kg)	<u>92</u>
Peso lordo (Kg)	<u>107</u>
Dimensioni imballo (l x l x h mm)	<u>750 x 650 x 1150(h) mm</u>
Volume imballo (m3)	<u>0.561</u>

Machine aimed at prolonging food preservation times, keeping intact the organoleptic characteristics and preventing the proliferation of bacteria at low temperatures. Stainless steel AISI 304 casing and internal bowl - bowl with rounded corners - plexiglass lid - automatic lid opening at the end of the cycle - LCD control panel with 20 storable programs - oil cleaning function in the pump and soft air function standard included. - piston sealing system with removable sealing bar without cables - provision for inert gas injection - BUSH pump (made in Germany) - "step vac" and "extra vacuum" functions included. Wheeled models. Use only smooth vacuum bags.



