## FRY TOP S Electric M80 AISI Plate - Smooth - Top

## **Version Thermostat**

**CODICE** CR1652459T MODELLO DT94/10TSFTEA SERIE DIAMANTE 90 TOUCH



#### **GENERAL CHARACTERISTICS**

Diamond 90 Touch - Everything under control Everything is under control, perfect results every time. Thanks to the practical display, parameter selection is quick and precise. Easy and clear temperature management, and special functions are always visible and accessible from the display. Tradition and innovation, everything on your worktop A new non-slip square and rounded knob design for a more ergonomic grip and an embossed indicator that makes it easier to select the datum to be set. And with the exclusive Encoder Functionality, simply touch the parameter you want, turn the knob to adjust the level and press it to start the set datum. With water- and dirt-proof crown. Quick and precise parameter selection. Easy and clear temperature management. Special functions always visible and accessible from the display. Stainless steel outer shells and feet. Height from the work surface adjustable from 840 to 900mm. Tops with 2 mm thickness

#### **TECHNICAL SPECIFICATIONS**

Cooking plate lowered from the top by 40 mm. Cooking plates made with a satin-finished surface and coated with soft iron or polished hard chrome, all available in smooth, mixed or ribbed versions. Plates inclined by 10mm towards the front of the machine.
Large grease collection drawer. Dimensions: 40, 60, 80, Heating by means of armoured incoloy heating elements. Thermostatically controlled and adjustable baking temperature from 110 to 280°C.
Safety thermostat.

• Floodable gutter for collecting cooking residues around the perimeter of the cooking plate easier cleaning and better retention

of moisture in cooking food I Large fat collection drawer with capacity of the entire volume of the perimeter channel I Grooved plate design ensures cleanliness right to the end of the plate I Plate not welded to the machine bed with optimisation of structural points under thermal stress I Plate not welded to the machine bed with optimisation of structural points under thermal stress I Thermal cutting that facilitates the user and adjacent machinery. I Uniform cooking temperature across the entire plate. Optimising heat in the cooking area and increasing operator comfort in the kitchen. Water dispenser kit available as an accessory





## **Version Thermostat**

**CODICE** CR1652459T **MODELLO** DT94/10TSFTEA SERIE DIAMANTE 90 TOUCH

### **Technical Information**

SPECIFICATION	DATA
MATERIAL	CR1652459T
COMMERCIAL LINE	DIAMANTE TOUCH
SUPPLY	ELECTRICS
DIM. WIDTH	800 mm
DIM. PRODUCTIVITY	900 mm
DIM. HEIGHT	250 mm
PACKAGE LENGTH	950 mm
PACKAGE WIDTH	850 mm
PACKAGING HEIGHT	500 mm
STANDARD POWER SUPPLY	380-415V 3N
FREQUENCY	50-60 Hz
ELECTRICAL POWER	15 kW
IP GRADE	IPX5
CERTIFIED MODEL	DT94/10TSFTEA






FRY TOP	S Electric	M80	AISI PI	late -	Smooth -	Тор
---------	------------	-----	---------	--------	----------	-----

## **Version Thermostat**

CODICE	IV
CR1652459T	D

/ODELLO DT94/10TSFTEA SERIE **DIAMANTE 90 TOUCH** 

### MISURE IN cm - DIMENSIONS IN cm - ABMESSUNGEN IN cm- MESURES EN cm MEDIDAS EN cm - MATEN IN cm - DIMENSIONES EN cm





Web: olis.it - Mail: info@olis.it




# FRY TOP S Electric M80 AISI Plate - Smooth - Top

## **Version Thermostat**

**CODICE** CR1652459T MODELLO DT94/10TSFTEA SERIE DIAMANTE 90 TOUCH





Floodable gutter for collecting cooking residues around the perimeter of the cooking plate easier cleaning and better retention of moisture in cooking food



Plate not welded to the machine bed with optimisation of structural points under thermal stress




Floodable gutter for collecting cooking residues around the perimeter of the cooking plate easier cleaning and better retention of moisture in cooking food



Plate not welded to the machine bed with optimisation of structural points under thermal stress




Large fat collection drawer with capacity of the entire volume of the perimeter channel



Thermal cutting that facilitates the user and adjacent machinery.



Grooved plate design ensures cleanliness right to the end of the plate



Uniform cooking temperature across the entire plate. Optimising heat in the cooking area and increasing operator comfort in the kitchen.



# FRY TOP S Electric M80 AISI Plate - Smooth - Top

## **Version Thermostat**

**CODICE** CR1652459T **MODELLO** DT94/10TSFTEA

### ACCESSORIES

CODE	MODELLO	DESCRIZIONE
CR1354989	PRPC	Smooth plate cleaning scraper - chrome-plated
CR1356399	RPR	Striped chrome plate scraper
CR1658629	D97CPFT68	Fry top cleaning drawer M60 - M80
CR1658609	97TFT	Plancha cleaning cap
CR1354999	PKLR	Replacement blades (10PCS)
CR1658689	9AFT8	M80 splash guard
CR1658709	D7968CAFT	WATER LOADING FOR FRY TOP M60 M80 - D70 D90 - GAS OR ELECTRIC
CR1658799	D98EKSCFT	CONTINUOUS DISCHARGE FOR FRY TOP M80 - D90 - ELECTRIC
CR1658829	D98ECSCFT	LOAD + SCAR.CONTINUOUS FOR FRY TOP M80 - D90 - ELECTRIC



