## 2-BURNER GAS COOKER ON OPEN BASE



CR0995119

MODELLO D92/10CG

DIAMANTE 90

SERIE



### **GENERAL CHARACTERISTICS**

In addition to offering the maximum choice of solutions and 2 mm thick and 90 cm deep tops, this series has all the power, robustness and functionality you need to work efficiently. External coatings and feet in stainless steel with Scotch Brite finish. Working table height adjustable from 840 to 900 mm. Range modularity: 200-400-600-800-1200 Wide range of accessories.

## **TECHNICAL SPECIFICATIONS**

- Upper burners with stabilised flame, made of nickel-plated cast iron.
   Thermocouple safety valves with pilot flame. Black acid-resistant enamelled cast iron grids with long spokes for holding small pans. AlSl304 stainless steel drip trays. Thanks to the jet-proofing certification (IPX5) obtained through specific tests, knobs and underknobs can be washed, without compromising functionality and safety.
   Nickel-plated cast-iron stabilised flame burners with double-crown spreader (improved performance facilitated by a flame distributed over two different sectors), Grid with long spokes to facilitate holding small pots and pans
- 90° venturi that prevents the nozzle from clogging and accumulating dirt. Nickel-plated cast-iron stabilised flame burners with double-crown spreader (improved performance facilitated by a flame distributed over two different sectors), Grid with long spokes to facilitate holding small pots and pans Removable AISI 304 stainless steel bowl for maximum hygiene. Thanks to the jet-proofing certification (IPX5) obtained through specific tests, knobs and under-knobs can be washed, without compromising functionality and safety.







**CODICE** CR0995119

MODELLO D92/10CG SERIE
DIAMANTE 90

# **Technical Information**

SPECIFICATION	DATA
MATERIAL	CR0995119
DEFINITION	D92/10 CG 2 FUOCHI VANO GIORNO
COMMERCIAL LINE	DIAMANTE
SUPPLY	GAS
DIM. WIDTH	400 mm
DIM. PRODUCTIVITY	900 mm
DIM. HEIGHT	870 mm
NETWEIGHT	48 Kg
VOLUME (net)	0.313
PACKAGE LENGTH	440 mm
PACKAGE WIDTH	1020 mm
PACKAGING HEIGHT	1160 mm
PACKAGE VOLUME	0,522 m3
GROSS PACKING WEIGHT	58 Kg
GAS POWER	10.5
GAS POWER (G25.3/25mbar)	9,00
N. FIRES/PLATES	DUE FUOCHI
CERTIFIED MODEL	D92/10 CG







CODICE CR0995119 MODELLO D92/10CG

DIAMANTE 90

#### SCHEMA DI INSTALLAZIONE - INSTALLATION DIAGRAM - INSTALLATIONSPLAN - SCHÉMA D'INSTALLATION -ESQUEMA DE INSTALACION -INSTALLATIESCHEMA - IINSTALLATIONSRITNINGAR


MISURE IN cm - DIMENSIONS IN cm - ABMESSUNGEN IN cm MESURES EN cm - MEDIDAS EN cm - MATEN IN cm


- (D) 92/10 TCG
- (D) 92/10 TCGP
- (D) 92/10 TCG1P















- (D) 92/10 CG
- (D) 92/10 CGP (D) 92/10 CG1P
- (D) 98/10 CG (D) 98/10 CGP
- (D) 98/10 CGG
  - (D) 98/10 CGGP
- (D) 98/10 CGE (D) 98/10 CGEP
- (D) 98/10 CG2P (D) 98/10 CGG2P (D) 98/10 CGE2P











Legenda - Legende - Key - Légende - Leyenda - Legenda

- Pressacavo entrata linea elettrica Stopfbuchse Electric cable stress relief - Presse étoupe de câble él Pisacable - Elektrische kabelwartel
- Attacco arrivo gas Gasanschluss Gas connection G Arrivée gaz - Union de gas - Gasaansluiting EN 10226-1 R 1/2; EN ISO 228-1 G 1/2 (DK)

H2O\* Attacco arrivo acqua - Wasseranschluss - Water inlet Arrivée eau - Union de agua - Wateraansluiting EN ISO 228-1 G 3/4



## 2-BURNER GAS COOKER ON OPEN BASE




CODICE CR0995119 MODELLO D92/10CG

DIAMANTE 90

SERIE



90° venturi that prevents the nozzle from clogging and accumulating dirt.



Nickel-plated cast-iron stabilised flame burners with double-crown spreader (improved performance facilitated by a flame distributed over two different sectors), Grid with long spokes to facilitate holding small pots and pans



Removable AISI 304 stainless steel bowl for maximum hygiene.



Thanks to the jet-proofing certification (IPX5) obtained through specific tests, knobs and under-knobs can be washed, without compromising functionality and safety.









CODICEMODELLOSERIECR0995119D92/10CGDIAMANTE 90

**ACCESSORIES** 

CODE	MODELLO	DESCRIZIONE
SUPBRUC	SUPBRUC	Supplement for burner 10 kw 10 (Kcal 8598.45)
MA97365000	GGN1/1	CHROME GRILLE GN1/1
MA97375000	GGN2/1	CHROME GRILLE GN2/1
MA97377000	BF9M-X	Chrome-plated steel grill for oven 93x62 cm MAXI
MA97376900	TGN2/1	AISI 304 stainless steel tray for oven 53x65x1 cm GN 2/1
MA97378000	BF9M-T	AISI 304 stainless steel baking tray for oven 93x62x1,5 cm MAXI
CR1353839	CR1353839	Smooth cast iron radiant plate 39.4x34.8 cm
CR1353849	CR1353849	Striped radiant plate 39.6x34.8 cm

