

MINI ELECTRIC SOLID TOP WITH TWO BURNERS ON THE RIGHT - TOP VERSION

CODICE
CR0995499

MODELLO
D94/10TCTGDX

SERIE
DIAMANTE 90



GENERAL CHARACTERISTICS

In addition to offering the maximum choice of solutions and 2 mm thick and 90 cm deep tops, this series has all the power, robustness and functionality you need to work efficiently. External coatings and feet in stainless steel with Scotch Brite finish. Working table height adjustable from 840 to 900 mm. Range modularity: 200-400-600-800-1200 Wide range of accessories.

TECHNICAL SPECIFICATIONS

■ Cast iron centre plate and ring. ■ Steel burner controlled by thermocouple safety valve. ■ Piezoelectric ignition with liquid-protected push button. ■ Adjustable temperature on the plate from 50° to 450°C. ■ Thermocouple safety valves with pilot flame.

■ Thick top plate with removable centre ring. ■ A single high-efficiency central burner that results in differentiated heat zones on the floor with a concentration of maximum heat in the centre and decreasing temperatures in the peripheral zones. ■ Thanks to the jet-proofing certification (IPX5) obtained through specific tests, knobs and under-knobs can be washed, without compromising functionality and safety.

MINI ELECTRIC SOLID TOP WITH TWO BURNERS ON THE RIGHT - TOP VERSION

CODICE
CR0995499

MODELLO
D94/10TCTGDX

SERIE
DIAMANTE 90

Technical Information


SPECIFICATION	DATA
MATERIAL	CR0995499
DEFINITION	D94/10 TCTGDX TUTTAPIAST.G.2 F DX TOP
COMMERCIAL LINE	DIAMANTE
SUPPLY	GAS
DIM. WIDTH	800 mm
DIM. PRODUCTIVITY	900 mm
DIM. HEIGHT	250 mm
NET WEIGHT	86 Kg
VOLUME (net)	0.18
PACKAGE LENGTH	840 mm
PACKAGE WIDTH	1020 mm
PACKAGING HEIGHT	550 mm
PACKAGE VOLUME	0,476 m3
GROSS PACKING WEIGHT	96 Kg
GAS POWER	17.5
GAS POWER (G25.3/25mbar)	15,50
CERTIFIED MODEL	D94/10 TCTGDX

MINI ELECTRIC SOLID TOP WITH TWO BURNERS ON THE RIGHT - TOP VERSION

CODICE	MODELLO	SERIE
CR0995499	D94/10TCTGDX	DIAMANTE 90

SCHEMA DI INSTALLAZIONE - INSTALLATION DIAGRAM - INSTALLATIONSPLAN - SCHÉMA D'INSTALLATION -
ESQUEMA DE INSTALACION -INSTALLATIESCHEMA - IINSTALLATIONSRIJNINGAR

MISURE IN cm - DIMENSIONS IN cm - ABMESSUNGEN IN cm
MESURES EN cm - MEDIDAS EN cm - MATEN IN cm



Legenda - Legende - Key - Légende - Leyenda - Legenda


- G** Attacco arrivo gas - Gasanschluss - Gas connection
Arrivée gaz - Union de gas - Gasaansluiting
EN 10226-1 R 1/2; EN ISO 228-1 G 1/2 (DK)
- H2O*** Attacco arrivo acqua - Wasseranschluss - Water inlet
Arrivée eau - Union de agua - Wateraansluiting
EN ISO 228-1 G 3/4

MINI ELECTRIC SOLID TOP WITH TWO BURNERS ON THE RIGHT - TOP VERSION

CODICE
CR0995499

MODELLO
D94/10TCTGDX

SERIE
DIAMANTE 90



Thick top plate with removable centre ring.



A single high-efficiency central burner that results in differentiated heat zones on the floor with a concentration of maximum heat in the centre and decreasing temperatures in the peripheral zones.



Thanks to the jet-proofing certification (IPX5) obtained through specific tests, knobs and under-knobs can be washed, without compromising functionality and safety.

MINI ELECTRIC SOLID TOP WITH TWO BURNERS ON THE RIGHT - TOP VERSION

CODICE
CR0995499

MODELLO
D94/10TCTGDX

SERIE
DIAMANTE 90

ACCESSORIES

CODE	MODELLO	DESCRIZIONE
CR1353839	CR1353839	Smooth cast iron radiant plate 39.4x34.8 cm
CR1353849	CR1353849	Striped radiant plate 39.6x34.8 cm