

# GAS SOLID TOP ON GAS OVEN WITH TWO BURNERS ON THE RIGHT

CODICE  
CR0995609

MODELLO  
D96/10CTGGDX

SERIE  
DIAMANTE 90



## GENERAL CHARACTERISTICS

In addition to offering the maximum choice of solutions and 2 mm thick and 90 cm deep tops, this series has all the power, robustness and functionality you need to work efficiently. External coatings and feet in stainless steel with Scotch Brite finish. Working table height adjustable from 840 to 900 mm. Range modularity: 200-400-600-800-1200 Wide range of accessories.

## TECHNICAL SPECIFICATIONS

■ Cast iron centre plate and ring. ■ Steel burner controlled by thermocouple safety valve. ■ Piezoelectric ignition with liquid-protected push button. ■ Adjustable temperature on the plate from 50° to 450°C. ■ Thermocouple safety valves with pilot flame.

■ Thick top plate with removable centre ring. ■ A single high-efficiency central burner that results in differentiated heat zones on the floor with a concentration of maximum heat in the centre and decreasing temperatures in the peripheral zones. ■ Thanks to the jet-proofing certification (IPX5) obtained through specific tests, knobs and under-knobs can be washed, without compromising functionality and safety.

# GAS SOLID TOP ON GAS OVEN WITH TWO BURNERS ON THE RIGHT

CODICE  
CR0995609

MODELLO  
D96/10CTGGDX

SERIE  
DIAMANTE 90

## Technical Information

SPECIFICATION	DATA
MATERIAL	CR0995609
DEFINITION	D96/10 CTGGDX TUTTAPIAST.G.F.G.+2F.DX
COMMERCIAL LINE	DIAMANTE
SUPPLY	GAS
DIM. WIDTH	1200 mm
DIM. PRODUCTIVITY	900 mm
DIM. HEIGHT	870 mm
NET WEIGHT	159 Kg
VOLUME (net)	0.94
PACKAGE LENGTH	1260 mm
PACKAGE WIDTH	1020 mm
PACKAGING HEIGHT	1150 mm
PACKAGE VOLUME	1,477 m3
GROSS PACKING WEIGHT	187 Kg
GAS POWER	32.5
GAS POWER (G25.3/25mbar)	28,90
CERTIFIED MODEL	D96/10 CTGGDX

# GAS SOLID TOP ON GAS OVEN WITH TWO BURNERS ON THE RIGHT

CODICE  
CR0995609

MODELLO  
D96/10CTGGDX

SERIE  
DIAMANTE 90

## SCHEMA DI INSTALLAZIONE - INSTALLATION DIAGRAM - INSTALLATIONSPLAN - SCHÉMA D'INSTALLATION - ESQUEMA DE INSTALACION -INSTALLATIESCHEMA - IINSTALLATIONSRTNINGAR

MISURE IN cm - DIMENSIONS IN cm - ABMESSUNGEN IN cm  
MESURES EN cm - MEDIDAS EN cm - MATEN IN cm



### Legenda - Legende - Key - Légende - Leyenda - Legenda

- E** Pressacavo entrata linea elettrica - Stopfbuchse  
Electric cable stress relief - Presse étoupe de câble él  
Pisacable - Elektrische kabelwartel
- G** Attacco arrivo gas - Gasanschluss - Gas connection  
Arrivée gaz - Union de gas - Gasaansluiting  
EN 10226-1 R 1/2; EN ISO 228-1 G 1/2 (DK)
- H2O\*** Attacco arrivo acqua - Wasseranschluss - Water inlet  
Arrivée eau - Union de agua - Wateraansluiting  
EN ISO 228-1 G 3/4

## GAS SOLID TOP ON GAS OVEN WITH TWO BURNERS ON THE RIGHT

CODICE  
CR0995609

MODELLO  
D96/10CTGGDX

SERIE  
DIAMANTE 90



Thick top plate with removable centre ring.



A single high-efficiency central burner that results in differentiated heat zones on the floor with a concentration of maximum heat in the centre and decreasing temperatures in the peripheral zones.



Thanks to the jet-proofing certification (IPX5) obtained through specific tests, knobs and under-knobs can be washed, without compromising functionality and safety.

## GAS SOLID TOP ON GAS OVEN WITH TWO BURNERS ON THE RIGHT

CODICE  
CR0995609

MODELLO  
D96/10CTGGDX

SERIE  
DIAMANTE 90

### ACCESSORIES

CODE	MODELLO	DESCRIZIONE
CR1353849	CR1353849	Striped radiant plate 39.6x34.8 cm
CR1353839	CR1353839	Smooth cast iron radiant plate 39.4x34.8 cm
MA97365000	GGN1/1	CHROME GRILLE GN1/1
MA97375000	GGN2/1	CHROME GRILLE GN2/1
MA97376900	TGN2/1	AISI 304 stainless steel tray for oven 53x65x1 cm GN 2/1
MA97378000	BF9M-T	AISI 304 stainless steel baking tray for oven 93x62x1,5 cm MAXI
MA97377000	BF9M-X	Chrome-plated steel grill for oven 93x62 cm MAXI