### **Version - Thermostat**

**CODICE** CR1651919 **MODELLO** D94/10TSFTTGA1/3R **SERIE** DIAMANTE 90





#### GENERAL CHARACTERISTICS

In addition to offering the maximum choice of solutions and 2 mm thick and 90 cm deep tops, this series has all the power, robustness and functionality you need to work efficiently. External coatings and feet in stainless steel with Scotch Brite finish. Working table height adjustable from 840 to 900 mm. Range modularity: 200-400-600-800-1200 Wide range of accessories.

#### **TECHNICAL SPECIFICATIONS**

■ 15 mm thick cooking plate totally independent of the hob. ■ Large floodable channel around the perimeter of the hotplate for collecting cooking residues, sloping towards the front for draining liquids into the large drawer. ■ Large grease collection drawer. ■ Uniform baking temperature over the entire plate. ■ Optimising heat in the cooking area and increasing the comfort of operators in the kitchen. ■ Plate not welded to the machine bed with optimisation of structural points under thermal stress ■ Stainless steel overflow plug, supplied as an accessory, for channel flooding management ■ Plate not welded to the machine bed with optimisation of structural points under thermal stress ■ New version with identical cooking surface area and reduced energy output. ■ An increase in output per cm2 allows a reduction in consumption of up to 15% compared to conventional versions ■ Tubular burner with self-stabilising flame with great uniformity of heat distribution.

■ Floodable gutter for collecting cooking residues around the perimeter of the cooking plate easier cleaning and better retention of moisture in cooking food ■ Large fat collection drawer with capacity of the entire volume of the perimeter channel ■ Grooved plate design ensures cleanliness right to the end of the plate ■ Plate not welded to the machine bed with optimisation of structural points under thermal stress ■ Plate not welded to the machine bed with optimisation of structural cutting that facilitates the user and adjacent machinery. ■ Uniform cooking temperature across the entire plate. Optimising heat in the cooking area and increasing operator comfort in the kitchen. ■ Water dispenser kit available as an accessory



## **Version - Thermostat**

**CODICE** CR1651919 **MODELLO** D94/10TSFTTGA1/3R **SERIE** DIAMANTE 90



#### **Technical Information**

| SPECIFICATION            | DATA                                     |
|--------------------------|------------------------------------------|
| MATERIAL                 | CR1651919                                |
| DEFINITION               | D94/10TSFTTGA1/3R FTG 1/3R 430 M80 T.TOP |
| COMMERCIAL LINE          | DIAMANTE                                 |
| SUPPLY                   | GAS                                      |
| DIM. WIDTH               | 800 mm                                   |
| DIM. PRODUCTIVITY        | 900 mm                                   |
| DIM. HEIGHT              | 250 mm                                   |
| NET WEIGHT               | 98 Kg                                    |
| VOLUME (net)             | 0.18                                     |
| PACKAGE LENGTH           | 840 mm                                   |
| PACKAGE WIDTH            | 1020 mm                                  |
| PACKAGING HEIGHT         | 550 mm                                   |
| PACKAGE VOLUME           | 0,476 m3                                 |
| GROSS PACKING WEIGHT     | 108 Kg                                   |
| GAS POWER                | 20                                       |
| GAS POWER (G25.3/25mbar) | 20,00                                    |
| CERTIFIED MODEL          | D94/10TSFTTG                             |






## **Version - Thermostat**

| CODICE    |   |
|-----------|---|
| CR1651919 | ) |

**MODELLO** D94/10TSFTTGA1/3R

**SERIE** DIAMANTE 90

### MISURE IN cm - DIMENSIONS IN cm - ABMESSUNGEN IN cm- MESURES EN cm MEDIDAS EN cm - MATEN IN cm - DIMENSIONES EN cm





Via Del Boscon, 424 - 32100 Belluno - Italy

Web: olis.it - Mail: info@olis.it

## **Version - Thermostat**

**CODICE** CR1651919 **MODELLO** D94/10TSFTTGA1/3R SERIE DIAMANTE 90 **DLIS** *We*innovate cooking



Floodable gutter for collecting cooking residues around the perimeter of the cooking plate easier cleaning and better retention of moisture in cooking food



Plate not welded to the machine bed with optimisation of structural points under thermal stress




Large fat collection drawer with capacity of the entire volume of the perimeter channel



Thermal cutting that facilitates the user and adjacent machinery.



Grooved plate design ensures cleanliness right to the end of the plate



Uniform cooking temperature across the entire plate. Optimising heat in the cooking area and increasing operator comfort in the kitchen.



Plate not welded to the machine bed with optimisation of structural points under thermal stress



Water dispenser kit available as an accessory



## **Version - Thermostat**

S

*We*innovate cooking

**CODICE** CR1651919 **MODELLO** D94/10TSFTTGA1/3R **SERIE** DIAMANTE 90

### ACCESSORIES

| CODE      | MODELLO   | DESCRIZIONE                                                   |
|-----------|-----------|---------------------------------------------------------------|
| CR1354989 | PRPC      | Smooth plate cleaning scraper - chrome-plated                 |
| CR1356399 | RPR       | Striped chrome plate scraper                                  |
| CR1658629 | D97CPFT68 | Fry top cleaning drawer M60 - M80                             |
| CR1658609 | 97TFT     | Plancha cleaning cap                                          |
| CR1354999 | PKLR      | Replacement blades (10PCS)                                    |
| CR1658689 | 9AFT8     | M80 splash guard                                              |
| CR1659249 | PAFT8     | M80 SUPER FRY TOP ACCESSORY HOLDER                            |
| CR1659379 | AKBFT-3   | KIT 1 BASIN GN1/3 H65 MM                                      |
| CR1659369 | AKBFT-2   | KIT 2 BOWLS GN1/6 H65 MM                                      |
| CR1659359 | AKBFT-1   | KIT 3 BOWLS GN1/9 H65 MM                                      |
| CR1659259 | AGMFT48   | HOLDING GRID FOR FRY TOP                                      |
| CR1659269 | AGMFT6    | HOLDING GRID FOR FRY TOP                                      |
| CR1658709 | D7968CAFT | WATER LOADING FOR FRY TOP M60 M80 - D70 D90 - GAS OR ELECTRIC |
| CR1659059 | D98GKSCFT | CONTINUOUS EXHAUST FOR FRY TOP M80 - D90 - GAS                |
| CR1659089 | D98GCSCFT | CONTINUOUS LOAD + SCAR.FOR FRY TOP M80 - D90 - GAS            |

