

INDIRECT GAS BOILING PAN 100lt - WITH AUTOMATIC CONDENSATE DRAIN VALVE

CODICE
CR1355999

MODELLO
D94/10PGI10S

SERIE
DIAMANTE 90



GENERAL CHARACTERISTICS

In addition to offering the maximum choice of solutions and 2 mm thick and 90 cm deep tops, this series has all the power, robustness and functionality you need to work efficiently. External coatings and feet in stainless steel with Scotch Brite finish. Working table height adjustable from 840 to 900 mm. Range modularity: 200-400-600-800-1200 Wide range of accessories.

TECHNICAL SPECIFICATIONS

■ AISI 304 stainless steel tanks with AISI 316 bottom. ■ Water loading by means of 2 solenoid valves, with the possibility of loading cold or hot water. ■ Frontal drain by means of 2" chrome-plated brass faucet. ■ Gas version: heating by means of 2 AISI 304 steel burners, positioned at the bottom of the vessel (direct heating) or in the cavity (indirect heating). ■ Indirect electric version: heating with 2 sets of armoured heating elements positioned inside the cavity. ■ Direct electric version: heating by means of 3 stainless steel heating elements positioned externally on the bottom of the container.

■ Possibility of hot or cold water loading ■ Stainless steel tank with aisi 316 bottom ■ Indirect pans with automatic condensate drain valve ■ Equipment certified for low voltage directive 2014/35/EU according to the international CB scheme. ■ Thanks to the jet-proofing certification (IPX5) obtained through specific tests, knobs and under-knobs can be washed, without compromising functionality and safety.

INDIRECT GAS BOILING PAN 100lt - WITH AUTOMATIC CONDENSATE DRAIN VALVE

CODICE
CR1355999

MODELLO
D94/10PGI10S

SERIE
DIAMANTE 90

Technical Information

SPECIFICATION	DATA
MATERIAL	CR1355999
DEFINITION	D94/10 PGI10 S PEN.GAS IND.M80 C/VAL100L
COMMERCIAL LINE	DIAMANTE
SUPPLY	MIXED
DIM. WIDTH	800 mm
DIM. PRODUCTIVITY	900 mm
DIM. HEIGHT	870 mm
NET WEIGHT	150.8 Kg
VOLUME (net)	0.626
PACKAGE LENGTH	860 mm
PACKAGE WIDTH	1020 mm
PACKAGING HEIGHT	1260 mm
PACKAGE VOLUME	1,105 m3
GROSS PACKING WEIGHT	160.8 Kg
STANDARD POWER SUPPLY	220-240V 1N
FREQUENCY	50 Hz
ELECTRICAL POWER	0.275 kW
GAS POWER	21
GAS POWER (G25.3/25mbar)	20,50
IP GRADE	IPX5
CERTIFIED MODEL	D94/10 PGI10
Capacity	100 litri

INDIRECT GAS BOILING PAN 100lt - WITH AUTOMATIC CONDENSATE DRAIN VALVE


CODICE
CR1355999

MODELLO
D94/10PGI10S

SERIE
DIAMANTE 90

SCHEMA DI INSTALLAZIONE - INSTALLATION DIAGRAM - INSTALLATIONSPLAN - SCHÉMA D'INSTALLATION - ESQUEMA DE INSTALACION - INSTALLATIESCHEMA - IINSTALLATIONSRIJNINGAR

MISURE IN cm - DIMENSIONS IN cm - ABMESSUNGEN IN cm
MESURES EN cm - MEDIDAS EN cm - MATEN IN cm



Legenda - Legende - Key - Légende - Leyenda - Legenda

H2O Attacchi arrivo acqua - Wasseranschluss - Water inlet - Arrivée eau - Union de agua - Wateraansluiting

A1 = Calda - Heiss - Warm - Chaud - Caliente - Warm

A2 = Fredda - Kalt - Cold - Froid - Fria - Koude

EN ISO 228-1 G 3/4

E Pressacavo entrata linea elettrica - Stopfbuchse - Electric cable stress relief

Presse étoupe de câble él. - Pisacable - Elektrische kabelwartel

G Attacco arrivo gas - Gasanschluss - Gas connection - Arrivée gaz - Union de gas - Gasaansluiting

EN 10226-1 R 1/2; EN ISO 228-1 G 1/2 (DK)

S Scarico acqua intercapedine - Wasserablauf Zwischenraum - Jacket water drain

Evacuation eau double enveloppe - Descarga de agua intersticios - Afvoer water tussenruimte

EN ISO 10226-1 R 3/4

S1 Scarico acqua - Wasserablauf - Water outlet - Vidange de l'eau - Desaguadero - Wateraftapaansluiting
2"

INDIRECT GAS BOILING PAN 100lt - WITH AUTOMATIC CONDENSATE DRAIN VALVE

CODICE
CR1355999

MODELLO
D94/10PGI10S

SERIE
DIAMANTE 90



Possibility of hot or cold water loading



Thanks to the jet-proofing certification (IPX5) obtained through specific tests, knobs and under-knobs can be washed, without compromising functionality and safety.



Stainless steel tank with aisi 316
bottom



Indirect pans with automatic
condensate drain valve

Equipment certified for low voltage
directive 2014/35/EU according to the
international CB scheme.



INDIRECT GAS BOILING PAN 100lt - WITH AUTOMATIC CONDENSATE DRAIN VALVE

CODICE
CR1355999

MODELLO
D94/10PGI10S

SERIE
DIAMANTE 90

ACCESSORIES

CODE	MODELLO	DESCRIZIONE
MA97347000	9C5	COLANDER BASKET
MA97348000	9CV5	VEGETABLE STRAINER BASKET FOR POT
MA97350900	9C10	COLANDER BASKET
MA97351000	9C15	COLANDER BASKET
MA97352000	9CV10	VEGETABLE STRAINER BASKET FOR POT
MA97353000	9CV15	VEGETABLE STRAINER BASKET FOR POT
MA97354000	9-I10	FUNNEL FOR POT DISCHARGE
MA97355000	9-I15	FUNNEL FOR POT DISCHARGE
MA97349000	9-I5	POWDER DISCHARGE INSTALLATION-50 Lt. HOLES Ø 10-15-36 MM