

# MINI GAS SOLID TOP ON OPEN BASE WITH TWO BURNERS ON THE RIGHT

CODICE  
CR0993659

MODELLO  
D74/10CTGDx

SERIE  
DIAMANTE 70



## GENERAL CHARACTERISTICS

In addition to offering the widest choice of solutions and 2 mm thick and 70 cm deep tops, this series has all the power, robustness and functionality you need to work efficiently. Scotch Brite finish stainless steel outer shells and feet. Worktop height adjustable from 840 to 900 mm. Modularity of range: 200-400-600-800-1200. Wide range of accessories.

## TECHNICAL SPECIFICATIONS

■ Cast iron centre plate and ring. ■ Aisi 304 steel burner controlled by safety valve and thermocouple. ■ Pilot flame, thermocouple, piezoelectric ignition and valved faucet ensure maximum safety.

■ Thick top plate with removable centre ring. ■ A single high-efficiency central burner that results in differentiated heat zones on

the floor with a concentration of maximum heat in the centre and decreasing temperatures in the peripheral zones. ■ Thanks to the jet-proofing certification obtained in specific tests, the knobs and under-knobs can be washed, without compromising functionality and safety.

# MINI GAS SOLID TOP ON OPEN BASE WITH TWO BURNERS ON THE RIGHT

CODICE  
CR0993659

MODELLO  
D74/10CTGDX

SERIE  
DIAMANTE 70

## Technical Information

SPECIFICATION	DATA
MATERIAL	CR0993659
DEFINITION	D74/10 CTGDX TUTTAPIAST.G.2F.DX+V.G.
COMMERCIAL LINE	DIAMANTE
SUPPLY	GAS
DIM. WIDTH	800 mm
DIM. PRODUCTIVITY	730 mm
DIM. HEIGHT	870 mm
NET WEIGHT	81 Kg
VOLUME (net)	0.508
PACKAGE LENGTH	850 mm
PACKAGE WIDTH	850 mm
PACKAGING HEIGHT	1150 mm
PACKAGE VOLUME	0,831 m3
GROSS PACKING WEIGHT	91 Kg
GAS POWER	15.1
GAS POWER (G25.3/25mbar)	13,70
GAS/REFRIGERANT TYPE	GPL 28-30/37 mbar
N. FIRES/PLATES	QUATTRO FUOCHI
CERTIFIED MODEL	D74/10 CTGDX

# MINI GAS SOLID TOP ON OPEN BASE WITH TWO BURNERS ON THE RIGHT


CODICE  
CR0993659

MODELLO  
D74/10CTGDX

SERIE  
DIAMANTE 70

## SCHEMA DI INSTALLAZIONE - INSTALLATION DIAGRAM - INSTALLATIONSPLAN - SCHÉMA D'INSTALLATION - ESQUEMA DE INSTALACION - INSTALLATIESCHEMA - IINSTALLATIONSRIJNINGAR

MISURE IN cm - DIMENSIONS IN cm - ABMESSUNGEN IN cm  
MESURES EN cm - MEDIDAS EN cm - MATEN IN cm



Legenda - Legende - Key - Légende - Leyenda - Legenda

**G** Attacco arrivo gas - Gasanschluss - Gas connection  
Arrivée gaz - Union de gas - Gasaansluiting  
**EN 10226-1 R 1/2; EN ISO 228-1 G 1/2 (DK)**

**H2O\*** Attacco arrivo acqua - Wasseranschluss - Water inlet  
Arrivée eau - Union de agua - Wateraansluiting  
**EN ISO 228-1 G 3/4**

## MINI GAS SOLID TOP ON OPEN BASE WITH TWO BURNERS ON THE RIGHT

CODICE  
CR0993659

MODELLO  
D74/10CTGDX

SERIE  
DIAMANTE 70



Thick top plate with removable centre ring.



A single high-efficiency central burner that results in differentiated heat zones on the floor with a concentration of maximum heat in the centre and decreasing temperatures in the peripheral zones.



Thanks to the jet-proofing certification (IPX5) obtained through specific tests, knobs and under-knobs can be washed, without compromising functionality and safety.

### ACCESSORIES

CODE	MODELLO	DESCRIZIONE
CR1353819	CR1353819	Smooth cast iron radiant plate