

CODICE CR0993709 **MODELLO** D74/10TCEPT

SERIE DIAMANTE 70



GENERAL CHARACTERISTICS

In addition to offering the widest choice of solutions and 2 mm thick and 70 cm deep tops, this series has all the power, robustness and functionality you need to work efficiently. Scotch Brite finish stainless steel outer shells and feet. Worktop height adjustable from 840 to 900 mm. Modularity of range: 200-400-600-800-1200 Wide range of accessories.

TECHNICAL SPECIFICATIONS

■ The range offers cookers with 220 mm round plates and 2.6 kW of power or 220x220 square plates and 2.6 kW fixed watertight on the worktop. ■ The temperature is adjusted by means of a 7-position selector switch, and a warning light indicating the activation of the

heating is located on the dashboard. Equipment certified for low voltage directive 2014/35/EU according to the international CB scheme. Thanks to the jet-proofing certification obtained in specific tests, the knobs and under-knobs can be washed, without compromising functionality and safety.





CODICE CR0993709 **MODELLO** D74/10TCEPT **SERIE** DIAMANTE 70

Technical Information

SPECIFICATION	DATA
MATERIAL	CR0993709
DEFINITION	D74/10 TCEPT 4 PIASTRE TONDE TOP
COMMERCIAL LINE	DIAMANTE
SUPPLY	ELECTRICS
DIM. WIDTH	800 mm
DIM. PRODUCTIVITY	730 mm
DIM. HEIGHT	250 mm
NETWEIGHT	77 Kg
VOLUME (net)	0.146
PACKAGE LENGTH	850 mm
PACKAGE WIDTH	850 mm
PACKAGING HEIGHT	570 mm
PACKAGE VOLUME	0,411 m3
GROSS PACKING WEIGHT	90 Kg
STANDARD POWER SUPPLY	380-415V 3N
FREQUENCY	50-60 Hz
ELECTRICAL POWER	10.4 kW
N. FIRES/PLATES	QUATTRO FUOCHI
TENSION	400
IP GRADE	IPX5
CERTIFIED MODEL	D74/10 TCEPT



to ISO 9001



CODICE CR0993709

MODELLO D74/10TCEPT **SERIE** DIAMANTE 70

SCHEMA DI INSTALLAZIONE - INSTALLATION DIAGRAM - INSTALLATIONSPLAN - SCHÉMA D'INSTALLATION -ESQUEMA DE INSTALACION -INSTALLATIESCHEMA - IINSTALLATIONSRITNINGAR

MISURE IN cm - DIMENSIONS IN cm - ABMESSUNGEN IN cm MESURES EN cm - MEDIDAS EN cm - MATEN IN cm (D) 72/10TCEP...T, Q (D) 74/10TCEP...T, Q (D) 76/10TCEPT • • 120* 58,5 (D) 72/10CEP...T, Q (D) 74/10CEP...T, Q (D) 76/10CEPT ام (D) 74/10CEEP....T, Q (D) 76/10CEEPT

Legenda - Legende - Key - Légende - Leyenda - Legenda

- E Pressacavo entrata linea elettrica Stopfbuchse Electric cable stress relief - Presse étoupe de câble él Pisacable - Elektrische kabelwartel
- H2O* Attacco arrivo acqua Wasseranschluss Water inlet Arrivée eau - Union de agua - Wateraansluiting EN ISO 228-1 G 3/4



CODICE CR0993709 MODELLO D74/10TCEPT **SERIE** DIAMANTE 70





The range offers cookers with 220 mm round plates and 2.6 kW of power or 220x220 square plates and 2.6 kW fixed watertight on the worktop.



The temperature is adjusted by means of a 7-position selector switch, and a warning light indicating the activation of the heating is located on the dashboard.



Equipment certified for low voltage directive 2014/35/EU according to the international CB scheme.



Thanks to the jet-proofing certification (IPX5) obtained through specific tests, knobs and under-knobs can be washed, without compromising functionality and safety.

