## ELECTRIC COOKER WITH 2 ROUND PLATES ON CABINET



**CODICE** CR0993749 MODELLO D72/10CEPT

**SERIE** DIAMANTE 70



#### **GENERAL CHARACTERISTICS**

In addition to offering the widest choice of solutions and 2 mm thick and 70 cm deep tops, this series has all the power, robustness and functionality you need to work efficiently. Scotch Brite finish stainless steel outer shells and feet. Worktop height adjustable from 840 to 900 mm. Modularity of range: 200-400-600-800-1200 Wide range of accessories.

#### **TECHNICAL SPECIFICATIONS**

Contoured dashboards with controls angled toward the operator.

■ The range offers cookers with 220 mm round plates and 2.6 kW of power or 220x220 square plates and 2.6 kW fixed watertight on the worktop. ■ The temperature is adjusted by means of a 7-position

selector switch, and a warning light indicating the activation of the heating is located on the dashboard. I Equipment certified for low voltage directive 2014/35/EU according to the international CB scheme. I Thanks to the jet-proofing certification obtained in specific tests, the knobs and under-knobs can be washed, without compromising functionality and safety.



# ELECTRIC COOKER WITH 2 ROUND PLATES ON CABINET



**CODICE** CR0993749 MODELLO D72/10CEPT **SERIE** DIAMANTE 70

#### **Technical Information**

SPECIFICATION	DATA
MATERIAL	CR0993749
DEFINITION	D72/10 CEPT 2 PIASTRE TONDE VANO G.
COMMERCIAL LINE	DIAMANTE
SUPPLY	ELECTRICS
DIM. WIDTH	400 mm
DIM. PRODUCTIVITY	730 mm
DIM. HEIGHT	870 mm
NETWEIGHT	65.8 Kg
VOLUME (net)	0.254
PACKAGE LENGTH	450 mm
PACKAGE WIDTH	850 mm
PACKAGING HEIGHT	1150 mm
PACKAGE VOLUME	0,440 m3
GROSS PACKING WEIGHT	75 Kg
STANDARD POWER SUPPLY	380-415V 3N
FREQUENCY	50-60 Hz
ELECTRICAL POWER	5.2 kW
N. FIRES/PLATES	QUATTRO FUOCHI
TENSION	400
IP GRADE	IPX5
CERTIFIED MODEL	D72/10 CEPT



### **ELECTRIC COOKER WITH 2 ROUND PLATES ON**

### CABINET

CODICE CR0993749 MODELLO D72/10CEPT SERIE **DIAMANTE 70** 

#### SCHEMA DI INSTALLAZIONE - INSTALLATION DIAGRAM - INSTALLATIONSPLAN - SCHÉMA D'INSTALLATION -ESQUEMA DE INSTALACION -INSTALLATIESCHEMA - IINSTALLATIONSRITNINGAR


MISURE IN cm - DIMENSIONS IN cm - ABMESSUNGEN IN cm MESURES EN cm - MEDIDAS EN cm - MATEN IN cm (D) 72/10TCEP...T, Q (D) 74/10TCEP...T, Q (D) 76/10TCEPT •• 120\* 58,5 (D) 74/10CEP...T, Q (D) 72/10CEP...T, Q (D) 76/10CEPT <del>ا</del>م (D) 74/10CEEP....T, Q (D) 76/10CEEPT 5

Legenda - Legende - Key - Légende - Leyenda - Legenda

- Е Pressacavo entrata linea elettrica - Stopfbuchse Electric cable stress relief - Presse étoupe de câble él Pisacable - Elektrische kabelwartel
- H2O\* Attacco arrivo acqua Wasseranschluss Water inlet Arrivée eau - Union de agua - Wateraansluiting EN ISO 228-1 G 3/4









# ELECTRIC COOKER WITH 2 ROUND PLATES ON CABINET

**CODICE** CR0993749 MODELLO D72/10CEPT **SERIE** DIAMANTE 70





The range offers cookers with 220 mm round plates and 2.6 kW of power or 220x220 square plates and 2.6 kW fixed watertight on the worktop.



The temperature is adjusted by means of a 7-position selector switch, and a warning light indicating the activation of the heating is located on the dashboard.



Equipment certified for low voltage directive 2014/35/EU according to the international CB scheme.



Thanks to the jet-proofing certification (IPX5) obtained through specific tests, knobs and under-knobs can be washed, without compromising functionality and safety.

