CIS Weinnovate cooking

CODICE CR0993799 MODELLO D74/10CEEPT **SERIE** DIAMANTE 70



GENERAL CHARACTERISTICS

In addition to offering the widest choice of solutions and 2 mm thick and 70 cm deep tops, this series has all the power, robustness and functionality you need to work efficiently. Scotch Brite finish stainless steel outer shells and feet. Worktop height adjustable from 840 to 900 mm. Modularity of range: 200-400-600-800-1200 Wide range of accessories.

TECHNICAL SPECIFICATIONS

Contoured dashboards with controls angled toward the operator.

■ The range offers cookers with 220 mm round plates and 2.6 kW of power or 220x220 square plates and 2.6 kW fixed watertight on the worktop. ■ The temperature is adjusted by means of a 7-position

selector switch, and a warning light indicating the activation of the heating is located on the dashboard. I Equipment certified for low voltage directive 2014/35/EU according to the international CB scheme. I Thanks to the jet-proofing certification obtained in specific tests, the knobs and under-knobs can be washed, without compromising functionality and safety.





CODICE CR0993799 MODELLO D74/10CEEPT **SERIE** DIAMANTE 70

Technical Information

SPECIFICATION	DATA
MATERIAL	CR0993799
DEFINITION	D74/10 CEEPT 4 PIASTRE TONDE + FORNO
COMMERCIAL LINE	DIAMANTE
SUPPLY	ELECTRICS
DIM. WIDTH	800 mm
DIM. PRODUCTIVITY	730 mm
DIM. HEIGHT	870 mm
NETWEIGHT	93 Kg
VOLUME (net)	0.508
PACKAGE LENGTH	840 mm
PACKAGE WIDTH	850 mm
PACKAGING HEIGHT	1170 mm
PACKAGE VOLUME	0,836 m3
GROSS PACKING WEIGHT	106 Kg
STANDARD POWER SUPPLY	380-415V 3N
FREQUENCY	50-60 Hz
ELECTRICAL POWER	16.4 kW
N. FIRES/PLATES	QUATTRO FUOCHI
TENSION	400
IP GRADE	IPX5
CERTIFIED MODEL	D74/10 CEEPT





CODICE CR0993799 MODELLO D74/10CEEPT **SERIE** DIAMANTE 70

SCHEMA DI INSTALLAZIONE - INSTALLATION DIAGRAM - INSTALLATIONSPLAN - SCHÉMA D'INSTALLATION -ESQUEMA DE INSTALACION -INSTALLATIESCHEMA - IINSTALLATIONSRITNINGAR

MISURE IN cm - DIMENSIONS IN cm - ABMESSUNGEN IN cm MESURES EN cm - MEDIDAS EN cm - MATEN IN cm (D) 72/10TCEP...T, Q (D) 74/10TCEP...T, Q (D) 76/10TCEPT •• 120* 58,5 (D) 74/10CEP...T, Q (D) 72/10CEP...T, Q (D) 76/10CEPT ام (D) 74/10CEEP....T, Q (D) 76/10CEEPT 5

Legenda - Legende - Key - Légende - Leyenda - Legenda

- E Pressacavo entrata linea elettrica Stopfbuchse Electric cable stress relief - Presse étoupe de câble él Pisacable - Elektrische kabelwartel
- H2O* Attacco arrivo acqua Wasseranschluss Water inlet Arrivée eau - Union de agua - Wateraansluiting EN ISO 228-1 G 3/4



Olis Ali Group S.r.l. Via Del Boscon, 424 - 32100 Belluno - Italy **Web**: olis.it - **Mail**: info@olis.it

CODICE CR0993799 MODELLO D74/10CEEPT **SERIE** DIAMANTE 70





The range offers cookers with 220 mm round plates and 2.6 kW of power or 220x220 square plates and 2.6 kW fixed watertight on the worktop.



The temperature is adjusted by means of a 7-position selector switch, and a warning light indicating the activation of the heating is located on the dashboard.



Equipment certified for low voltage directive 2014/35/EU according to the international CB scheme.



Thanks to the jet-proofing certification (IPX5) obtained through specific tests, knobs and under-knobs can be washed, without compromising functionality and safety.





CODICE CR0993799 **MODELLO** D74/10CEEPT

SERIE DIAMANTE 70

ACCESSORIES

CODE	MODELLO	DESCRIZIONE
MA97378000	BF9M-T	AISI 304 stainless steel baking tray for oven 93x62x1,5 cm MAXI
MA97376900	TGN2/1	AISI 304 stainless steel tray for oven 53x65x1 cm GN 2/1
MA97377000	BF9M-X	Chrome-plated steel grill for oven 93x62 cm MAXI

