

## 4-ZONE ELECTRIC GLASS-CERAMIC COOKER

CODICE  
CR0990239

MODELLO  
D74/10TVTC

SERIE  
DIAMANTE 70



### GENERAL CHARACTERISTICS

In addition to offering the widest choice of solutions and 2 mm thick and 70 cm deep tops, this series has all the power, robustness and functionality you need to work efficiently. Scotch Brite finish stainless steel outer shells and feet. Worktop height adjustable from 840 to 900 mm. Modularity of range: 200-400-600-800-1200. Wide range of accessories.

### TECHNICAL SPECIFICATIONS

■ Cooking zones marked with circular silk-screen printing 23 cm in diameter. ■ 2.5 kW single zone power. ■ The temperature is adjusted by energy regulator, which allows the width of the heating zone to be selected according to the size of the bottom of the pot.

■ Unbreakable flush-mounted glass for easy handling of pans. ■ A temperature regulator sets the temperature and this permits to select two sizes of the heating zone according to the size of the pot bottom. ■ Equipment certified for low voltage directive 2014/35/EU

according to the international CB scheme. ■ Thanks to the jet-proofing certification obtained in specific tests, the knobs and under-knobs can be washed, without compromising functionality and safety. ■ Plates with safety thermostat that automatically activates in case of no-load or over-temperature use. ■ Hermetically sealed 6 mm thick glass-ceramic cooktop with four independent cooking zones. Each zone includes a circular radiant element with a diameter of 230 mm and an output of 2.5 kW.

## 4-ZONE ELECTRIC GLASS-CERAMIC COOKER

CODICE  
CR0990239

MODELLO  
D74/10TVTC

SERIE  
DIAMANTE 70

### Technical Information

SPECIFICATION	DATA
MATERIAL	CR0990239
DEFINITION	D74/10 TVTC VETROCERAMICA 4Z. TOP
COMMERCIAL LINE	DIAMANTE
SUPPLY	ELECTRICS
DIM. WIDTH	800 mm
DIM. PRODUCTIVITY	730 mm
DIM. HEIGHT	250 mm
NET WEIGHT	37 Kg
VOLUME (net)	0.146
PACKAGE LENGTH	850 mm
PACKAGE WIDTH	850 mm
PACKAGING HEIGHT	570 mm
PACKAGE VOLUME	0,411 m3
GROSS PACKING WEIGHT	44.4 Kg
STANDARD POWER SUPPLY	380-415V 3N
FREQUENCY	50-60 Hz
ELECTRICAL POWER	10 kW
IP GRADE	IPX4
CERTIFIED MODEL	D74/10 TVTC

# 4-ZONE ELECTRIC GLASS-CERAMIC COOKER


CODICE  
CR0990239

MODELLO  
D74/10TVTC

SERIE  
DIAMANTE 70

## SCHEMA DI INSTALLAZIONE - INSTALLATION DIAGRAM - INSTALLATIONSPLAN - SCHÉMA D'INSTALLATION - ESQUEMA DE INSTALACION - INSTALLATIESCHEMA - IINSTALLATIONSRTNINGAR

MISURE IN cm - DIMENSIONS IN cm - ABMESSUNGEN IN cm  
MESURES EN cm - MEDIDAS EN cm - MATEN IN cm



Legenda - Legende - Key - Légende - Leyenda - Legenda

**E** Pressacavo entrata linea elettrica - Stopfbuchse - Electric cable stress relief  
Presse étoupe de câble él. - Pisacable - Elektrische kabelwartel

**H2O\*** Attacco arrivo acqua - Wasseranschluss - Water inlet  
Arrivée eau - Union de agua - Wateraansluiting  
**EN ISO 228-1 G 1/2**

## 4-ZONE ELECTRIC GLASS-CERAMIC COOKER

CODICE  
CR0990239

MODELLO  
D74/10TVTC

SERIE  
DIAMANTE 70



Unbreakable flush-mounted glass for easy handling of pans.



A temperature regulator sets the temperature and this permits to select two sizes of the heating zone according to the size of the pot bottom.



Equipment certified for low voltage directive 2014/35/EU according to the international CB scheme.



Thanks to the jet-proofing certification (IPX5) obtained through specific tests, knobs and under-knobs can be washed, without compromising functionality and safety.