

CODICE CR1359219 **MODELLO** D72/10TCIIW

SERIE DIAMANTE 70



GENERAL CHARACTERISTICS

In addition to offering the widest choice of solutions and 2 mm thick and 70 cm deep tops, this series has all the power, robustness and functionality you need to work efficiently. Scotch Brite finish stainless steel outer shells and feet. Worktop height adjustable from 840 to 900 mm. Modularity of range: 200-400-600-800-1200 Wide range of accessories.

TECHNICAL SPECIFICATIONS

■ Unbreakable glass-ceramic top. ■ Serigraphs identifying cooking zones. ■ Safety sensor to prevent overheating. ■ Power adjustable to 12 levels ■ Heating by means of an inductor equipped with a device that detects the presence of the cooking vessel on the cooking zone and automatically switches the heating on/off, and a device against overheating.

■ Possibility of setting 2 timers to control cooking. An acoustic signal warns the operator at the end of the set time. ■ Power level control

via touch screen and adjustment with ergonomic knob I High power, full-field capability. automatic detection of the presence of pans. I Everything is under control, perfect results every time. Thanks to the practical display, parameter selection is quick and precise. Easy and clear temperature management, and special functions are always visible and accessible from the display. I Thanks to the jetproofing certification (IPX5) obtained through specific tests, knobs and under-knobs can be washed, without compromising functionality and safety.





CODICE CR1359219 **MODELLO** D72/10TCIIW

SERIE DIAMANTE 70

Technical Information

SPECIFICATION	DATA
MATERIAL	CR1359219
DEFINITION	D72/10 TCIW WOK M40
COMMERCIAL LINE	DIAMANTE
SUPPLY	ELECTRICS
DIM. WIDTH	400 mm
DIM. PRODUCTIVITY	730 mm
DIM. HEIGHT	250 mm
NETWEIGHT	53.8 Kg
VOLUME (net)	0.073
PACKAGE LENGTH	450 mm
PACKAGE WIDTH	850 mm
PACKAGING HEIGHT	1150 mm
PACKAGE VOLUME	0,450 m3
GROSS PACKING WEIGHT	63 Kg
STANDARD POWER SUPPLY	400V 3
FREQUENCY	50/60 Hz
ELECTRICAL POWER	5 kW
IP GRADE	IPX4
CERTIFIED MODEL	D72/10 TCIW WOK M40





CODICE CR1359219 MODELLO D72/10TCIIW

SERIE DIAMANTE 70

SCHEMA DI INSTALLAZIONE - INSTALLATION DIAGRAM - INSTALLATIONSPLAN - SCHÉMA D'INSTALLATION -ESQUEMA DE INSTALACION -INSTALLATIESCHEMA - IINSTALLATIONSRITNINGAR

MISURE IN cm - DIMENSIONS IN cm - ABMESSUNGEN IN cm MESURES EN cm - MEDIDAS EN cm - MATEN IN cm





(D)72/10 GCIW

...

(D)72/10 TCI


(D)72/10 CI


(D)72/10 GCI





(D)74/10 TCI


(D)74/10 CI (D)74/10 GCI











Legenda - Legende - Key - Légende - Leyenda - Legenda

4.5

- E Pressacavo entrata linea elettrica Stopfbuchse Electric cable stress relief Presse étoupe de câble él. - Pisacable - Elektrische kabelwartel
- H2O* Attacco arrivo acqua Wasseranschluss Water inlet Arrivée eau - Union de agua - Wateraansluiting EN ISO 228-1 G 3/4



CODICE CR1359219 **MODELLO** D72/10TCIIW **SERIE** DIAMANTE 70





Possibility of setting 2 timers to control cooking. An acoustic signal warns the operator at the end of the set time.



Thanks to the jet-proofing certification (IPX5) obtained through specific tests, knobs and under-knobs can be washed, without compromising functionality and safety.



Power level control via touch screen and adjustment with ergonomic knob



High power, full-field capability. automatic detection of the presence of pans.



Everything is under control, perfect results every time. Thanks to the practical display, parameter selection is quick and precise. Easy and clear temperature management, and special functions are always visible and accessible from the display.

