

43lt GAS MANUAL BRATT PAN WITH STAINLESS STEEL BOTTOM

CODICE
CR0989969

MODELLO
D74/10KBGI

SERIE
DIAMANTE 70



GENERAL CHARACTERISTICS

In addition to offering the widest choice of solutions and 2 mm thick and 70 cm deep tops, this series has all the power, robustness and functionality you need to work efficiently. Scotch Brite finish stainless steel outer shells and feet. Worktop height adjustable from 840 to 900 mm. Modularity of range: 200-400-600-800-1200. Wide range of accessories.

TECHNICAL SPECIFICATIONS

■ Multifunctional tilting braising pan, equipment for professional catering, suitable for cooking sauces, braises and cooking with oil. ■ It guarantees high performance, exceptional firing uniformity. ■ Water supply directly into the tank via solenoid valve (can be ordered as an accessory). ■ Cooking temperature controlled by thermostat with adjustment from 100 to 280°C.

■ Stainless steel cooking vessel, 10 mm thick. ■ Cooking temperature controlled by thermostat with adjustment from 100 to 280°C. ■

Heating by chrome-plated steel burner. ■ Safety valve with thermocouple, electric ignition. ■ Robust, double-walled, self-balancing lids made of stainless steel to reduce heat loss. ■ Large-radius tilting tank. ■ Equipment certified for low voltage directive 2014/35/EU according to the international CB scheme. ■ Thanks to the jet-proofing certification (IPX5) obtained through specific tests, knobs and under-knobs can be washed, without compromising functionality and safety.

43lt GAS MANUAL BRATT PAN WITH STAINLESS STEEL BOTTOM

CODICE
CR0989969

MODELLO
D74/10KBGI

SERIE
DIAMANTE 70

Technical Information

SPECIFICATION	DATA
MATERIAL	CR0989969
DEFINITION	D74/10 KBGI BRASIERA GAS M80 INOX
COMMERCIAL LINE	DIAMANTE
SUPPLY	GAS
DIM. WIDTH	800 mm
DIM. PRODUCTIVITY	730 mm
DIM. HEIGHT	870 mm
NET WEIGHT	114.8 Kg
VOLUME (net)	0.508
PACKAGE LENGTH	850 mm
PACKAGE WIDTH	850 mm
PACKAGING HEIGHT	1150 mm
PACKAGE VOLUME	0,831 m3
GROSS PACKING WEIGHT	124 Kg
STANDARD POWER SUPPLY	220-240V 1N
FREQUENCY	50 Hz
ELECTRICAL POWER	0.12 kW
GAS POWER	14
GAS POWER (G25.3/25mbar)	13,00
CERTIFIED MODEL	D74/10 KBGI

43lt GAS MANUAL BRATT PAN WITH STAINLESS STEEL BOTTOM


CODICE
CR0989969

MODELLO
D74/10KBGI


SERIE
DIAMANTE 70

SCHEMA DI INSTALLAZIONE - INSTALLATION DIAGRAM - INSTALLATIONSPLAN - SCHÉMA D'INSTALLATION - ESQUEMA DE INSTALACION - INSTALLATIESCHEMA - IINSTALLATIONSRTNINGAR

MISURE IN cm - DIMENSIONS IN cm - ABMESSUNGEN IN cm
MESURES EN cm - MEDIDAS EN cm - MATEN IN cm



(D) 74/10 KBG ...



Legenda - Legende - Key - Légende - Leyenda - Legenda

- G** Attacco arrivo gas - Gasanschluss - Gas connection
Arrivée gaz - Union de gas - Gasaansluiting
EN 10226-1 R 1/2; EN ISO 228-1 G 1/2 (DK)
- S** Scarico vasca - Wannenabflussrohr - Pan outlet
Vidange du bac - Descarga cuba - Water toevoer

43lt GAS MANUAL BRATT PAN WITH STAINLESS STEEL BOTTOM

CODICE
CR0989969

MODELLO
D74/10KBGI

SERIE
DIAMANTE 70



Self-balancing lids.



Large-radius tilting tank.



Thanks to the jet-proofing certification (IPX5) obtained through specific tests, knobs and under-knobs can be washed, without compromising functionality and safety.


43lt GAS MANUAL BRATT PAN WITH STAINLESS STEEL BOTTOM

CODICE
CR0989969

MODELLO
D74/10KBGI

SERIE
DIAMANTE 70

OPTIONAL

MODELLO	DESCRIZIONE
	XCAKBG

ACCESSORIES

CODE	MODELLO	DESCRIZIONE
CR0954719	XCAKBG	