

CR0989979

MODELLOD74/10KBE

DIAMANTE 70

SERIE



GENERAL CHARACTERISTICS

In addition to offering the widest choice of solutions and 2 mm thick and 70 cm deep tops, this series has all the power, robustness and functionality you need to work efficiently.

Scotch Brite finish stainless steel outer shells and feet.

Worktop height adjustable from 840 to 900 mm.

Modularity of range: 200-400-600-800-1200

Wide range of accessories.

TECHNICAL SPECIFICATIONS

- Multifunctional tilting braising pan, equipment for professional catering, suitable for cooking sauces, braises and cooking with oil. It guarantees high performance, exceptional firing uniformity. Water supply directly into the tank via solenoid valve (can be ordered as an accessory). Cooking temperature controlled by thermostat with adjustment from 100 to 280°C.
- IRON baking tray (available for non-EU markets) with 2 mm thickness. Cooking temperature controlled by thermostat with

adjustment from 100 to 280°C. Heating via armoured incoloy heating elements. ■ Robust, double-walled, self-balancing lids made of stainless steel to reduce heat loss. ■ Large-radius tilting tank. ■ Equipment certified for low voltage directive 2014/35/EU according to the international CB scheme. ■ Thanks to the jet-proofing certification obtained through specific tests, the knobs and underknobs can be washed, without compromising functionality and safety.





CODICE CR0989979 **MODELLO**D74/10KBE

SERIEDIAMANTE 70

Technical Information

| CDECIFICATION | 2.77 |
|-----------------------|-------------------------------|
| SPECIFICATION | DATA |
| MATERIAL | CR0989979 |
| DEFINITION | D74/10 KBE BRASIERA EL.M80 FE |
| COMMERCIAL LINE | DIAMANTE |
| SUPPLY | ELECTRICS |
| DIM. WIDTH | 800 mm |
| DIM. PRODUCTIVITY | 730 mm |
| DIM. HEIGHT | 870 mm |
| NETWEIGHT | 119.8 Kg |
| VOLUME (net) | 0.508 |
| PACKAGE LENGTH | 850 mm |
| PACKAGE WIDTH | 850 mm |
| PACKAGING HEIGHT | 1150 mm |
| PACKAGE VOLUME | 0,831 m3 |
| GROSS PACKING WEIGHT | 130 Kg |
| STANDARD POWER SUPPLY | 380-415V 3N |
| FREQUENCY | 50-60 Hz |
| ELECTRICAL POWER | 9.9 kW |
| IP GRADE | IPX4 |
| CERTIFIED MODEL | D74/10 KBE |





CODICE CR0989979 MODELLO


D74/10KBE


DIAMANTE 70

SERIE


SCHEMA DI INSTALLAZIONE - INSTALLATION DIAGRAM - INSTALLATIONSPLAN - SCHÉMA D'INSTALLATION - ESQUEMA DE INSTALACION -INSTALLATIESCHEMA - IINSTALLATIONSRITNINGAR

MISURE IN cm - DIMENSIONS IN cm - ABMESSUNGEN IN cm MESURES EN cm - MEDIDAS EN cm - MATEN IN cm









Legenda - Legende - Key - Légende - Leyenda - Legenda

- **E** Pressacavo entrata linea elettrica Stopfbuchse Electric cable stress relief Presse étoupe de câble él. Pisacable Elektrische kabelwartel
- S Scarico vasca Wannenabflussrohr Pan outlet Vidange du bac Descarga cuba Water toevoer









CODICE CR0989979 **MODELLO**D74/10KBE

DIAMANTE 70

SERIE



Self-balancing lids.



Large-radius tilting tank.



Equipment certified for low voltage directive 2014/35/EU according to the international CB scheme.



Thanks to the jet-proofing certification (IPX5) obtained through specific tests, knobs and under-knobs can be washed, without compromising functionality and safety.







CODICE

MODELLO

SERIE

CR0989979

D74/10KBE

DIAMANTE 70

OPTIONAL

| | MODELLO | DESCRIZIONE |
|-----|---------|-------------|
| 2.6 | ХСАКВЕ | |

ACCESSORIES

| CODE | MODELLO | DESCRIZIONE |
|-----------|---------|-------------|
| CR0954729 | XCAKBE | |



