DLIS *We*innovate cooking

CODICE CR0989919 **MODELLO** D72/10KBEF

SERIE DIAMANTE 70



GENERAL CHARACTERISTICS

In addition to offering the widest choice of solutions and 2 mm thick and 70 cm deep tops, this series has all the power, robustness and functionality you need to work efficiently. Scotch Brite finish stainless steel outer shells and feet. Worktop height adjustable from 840 to 900 mm. Modularity of range: 200-400-600-800-1200 Wide range of accessories.

TECHNICAL SPECIFICATIONS

■ Tank made entirely of AISI 304 steel. ■ Heating ensured by armoured heating elements positioned outside the tank bottom. ■ The temperature, thermostatically controlled, is adjustable from 50 to 300 °C. ■ Stainless steel outer shells and feet.

■ Equipment certified for low voltage directive 2014/35/EU according to the international CB scheme. ■ Thanks to the jetproofing certification obtained in specific tests, the knobs and under-knobs can be washed, without compromising functionality and safety.





CODICE CR0989919 MODELLO D72/10KBEF **SERIE** DIAMANTE 70

Technical Information

SPECIFICATION	DATA
MATERIAL	CR0989919
DEFINITION	D72/10 KBEF MULTIPLA M40
COMMERCIAL LINE	DIAMANTE
SUPPLY	ELECTRICS
DIM. WIDTH	400 mm
DIM. PRODUCTIVITY	730 mm
DIM. HEIGHT	870 mm
NETWEIGHT	50 Kg
VOLUME (net)	0.254
PACKAGE LENGTH	440 mm
PACKAGE WIDTH	850 mm
PACKAGING HEIGHT	1030 mm
PACKAGE VOLUME	0,400 m3
GROSS PACKING WEIGHT	58 Kg
STANDARD POWER SUPPLY	380-415V 3N
FREQUENCY	50-60 Hz
ELECTRICAL POWER	4.05 kW
IP GRADE	IPX4
CERTIFIED MODEL	D72/10 KBEF








CODICE CR0989919 MODELLO D72/10KBEF **SERIE** DIAMANTE 70


SCHEMA DI INSTALLAZIONE - INSTALLATION DIAGRAM - INSTALLATIONSPLAN - SCHÉMA D'INSTALLATION -ESQUEMA DE INSTALACION -INSTALLATIESCHEMA - IINSTALLATIONSRITNINGAR

MISURE IN cm - DIMENSIONS IN cm - ABMESSUNGEN IN cm MESURES EN cm - MEDIDAS EN cm - MATEN IN cm









Legenda - Legende - Key - Légende - Leyenda - Legenda

- E Pressacavo entrata linea elettrica Stopfbuchse Electric cable stress relief Presse étoupe de câble él. - Pisacable - Elektrische kabelwartel
- S Scarico vasca Wannenabflussrohr Pan outlet Vidange du bac - Descarga cuba - Water toevoer
- H2O* Attacco arrivo acqua Wasseranschluss Water inlet Arrivée eau - Union de agua - Wateraansluiting EN ISO 228-1 G 3/4



CODICE CR0989919 **MODELLO** D72/10KBEF **SERIE** DIAMANTE 70



Equipment certified for low voltage directive 2014/35/EU according to the international CB scheme.



Thanks to the jet-proofing certification (IPX5) obtained through specific tests, knobs and under-knobs can be washed, without compromising functionality and safety.

