

CR0854379

MODELLO OVB66E **SERIE** SERIE 650



GENERAL CHARACTERISTICS

The OLIS SNACK 650 range has a design that characterises all equipment in both top and monoblock versions, with large knobs and an ergonomic dashboard shape.

The wide choice of machines and high performance make this range the ideal choice for environments that are not very spacious but still require high-performance machines.

The modularity of the range allows infinite combinations with installation on compartment bases or tables.

TECHNICAL SPECIFICATIONS

■ MULTI-FUNCTION SINGLE-BLOCK BRATT PAN Equipment ideal for use as both a fry-top and a braising pan and is equipped with an AISI 304 stainless steel tank. Heating is by electric heating element with

safety thermostat and operation indicator light. Drainage of the tank is by means of drain hole of suitable diameter closed by stainless steel plug. • The multiple, with a tank made entirely of AISI 304 stainless steel, has heating elements placed under the bottom of the tank for even temperature distribution adjustable from 110 to 280°C.





CODICE CR0854379 MODELLO OVB66E **SERIE** SERIE 650

Technical Information

SPECIFICATION	DATA
MATERIAL	CR0854379
DEFINITION	MULTIPLA EL.60 M60 OVB66E
COMMERCIAL LINE	SERIE 600
SUPPLY	ELECTRICS
DIM. WIDTH	600 mm
DIM. PRODUCTIVITY	600 mm
DIM. HEIGHT	870 mm
NETWEIGHT	63.7 Kg
VOLUME (net)	0.313
PACKAGE LENGTH	690 mm
PACKAGE WIDTH	690 mm
PACKAGING HEIGHT	1050 mm
PACKAGE VOLUME	0,500 m3
GROSS PACKING WEIGHT	71 Kg
STANDARD POWER SUPPLY	380-415V 3N
FREQUENCY	50-60 Hz
ELECTRICAL POWER	8.1 kW
IP GRADE	IPX4
CERTIFIED MODEL	OVB66E








CODICEMODELLOSERIECR0854379OVB66ESERIE 650

SCHEMA DI INSTALLAZIONE - INSTALLATION DIAGRAM - INSTALLATIONSPLAN - SCHÉMA D'INSTALLATION - ESQUEMA DE INSTALLACION -INSTALLATIESCHEMA - IINSTALLATIONSRITNINGAR

MISURE IN mm - DIMENSIONS IN mm - ABMESSUNGEN IN mm MESURES EN mm - MEDIDAS EN mm - MATEN IN mm







LEGENDA - LEGENDE - KEY - LEGENDE - LEYENDA - LEGENDA

E Pressacavo entrata linea elettrica - Stopfbuchse - Electric cable stress relief - Presse etoupr de cable el Pisacable - Elektrische kabelwartel





CODICEMODELLOSERIECR0854379OVB66ESERIE 650



The multiple, with a tank made entirely of AISI 304 stainless steel, has heating elements placed under the bottom of the tank for even temperature distribution adjustable from 110 to 280°C.



